



LUPUSNET HD - LE930

Art. 100142

- › 2 Megapixel Chip, max. 1600x1200 Pixel (@ 15 FPS)
- › 720P @ 30FPS
- › Max. 20 m night vision range
- › Powerful H.264-compression
- › WiFi and Ethernet connection
- › 3GPP Live-Streaming to mobile phones
- › Day/ night vision with IR-Cut Filter
- › Movement detection + alert notification
- › FTP-upload, live stream web integration

MAIN FEATURES

Professional 2 megapixel video surveillance day and night bei Tag und Nacht: The brand new LUPUSNET HD - LE930 with its 1600x1200 Pixel resolution @15 FPS and realtime transmission (30 FPS) @ 720P (HD Ready) resolution will meet pretty much every requirement. Its fantastic equipment combined with its very reasonable pricing and very easy installation makes this camera a reliable ally for every challenge. The camera is equipped with high performance IR-LEDs and delivers crisp sharp high resolution night vision images up to 20 meters. Together with its weatherproof construction, it's just the perfect solution for outdoor surveillance. And its powerful H.264 compression capabilities, WiFi and Ethernet connection, 3GPP Streaming and many more allow for an outstanding communication performance in every network.

HARDWARE

CPU	ARM 9, 32 bit RISC
RAM	256MB
Flash	16MB
Image Sensor	1/3,2" (7,9mm) CMOS (2 Megapixel)
Min. lighting conditions	0 lux (IR On)
Supports DC IRIS	Yes
I/O	1 Relay In /1 Relay Out
Lens	Vari-focal 3.6~16mm Megapixel Lens
ICR	IR cut Filter
LED	Integrated 35 high performance IR LEDs
Night vision range	20m
RS-485	Yes
Video Out	1
Audio In	1
Audio Out	1
Power over Ethernet (PoE)	Yes
Power consumption	DC 12V 500 mA
Operating temperature	-20°C ~40°C
Dimensions	83mm (Ø) x 1800 (D)

NETWORK

Network protocol	HTTP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP
Ethernet	10/ 100 Base-T
Wireless	802.11b/g
Security	WEP, WPA-PSK, WPA2-PSK

SYSTEM

Video resolution	1600x1200, 1280x1024, 1280x960, 1280x720, 800x600, 640x480, 320x240, 176x144
Video adjustment	Brightness, contrast, sharpness, BLC, night mode
Triple streaming	Yes
Screenshots	Yes
Fullscreen	Yes
Privacy mask	Yes, 3 areas
Compression format	H.264/ MJPEG/ MPEG4 (3GPP only)
Video bitrates adjustment	CBR, VBR
Movement detection	Yes, 3 areas
Actionable items	Mail, FTP, save to SD card, relay out
Pre/ post alarm	Yes, adjustable
Security	Password secured
Firmware upgrade	HTTP Mode, supports upgrade via remote control
Multi user access	Yes, up to 10 parallel users
Audio	Yes, 2-way

SYSTEM REQUIREMENTS

Operating system	Windows 2000, XP, 2003, Microsoft IE 6.0 or higher
Hardware recommended	Intel Dual Core 1.66G, RAM: 1024MB, graphics card: 128MB
Hardware minimum	Intel-C 2,8G, RAM:512MB, graphics card: 64MB

SCOPE OF DELIVERY

LupusnetHD Network camera model	LE930
Mount	Included
Power adapter	12V 1A
Software	LupusnetHD Lite
User Manual	Quick User Manual for camera, User manual for Software and camera on CD

Your LUPUS Certified Partner:

