



LUPUSNET HD - LE950

Art. 10950

- › 1.3 Megapixel Sensor (1280x1024 Pixel)
- › MPEG4/MJPEG compression
- › WiFi and Ethernet connection
- › 2-way audio transmission
- › 3GPP Live-Streaming to mobile phones
- › Movement detection + alert notification
- › FTP-upload, live stream web integration
- › Free LUPUSNET HD Lite 32 CH Recording-Software included

MAIN FEATURES

Compact, discreet video surveillance with megapixel resolution: Like all cameras of the LUPUSNET HD-Series, the LUPUSNET HD - LE950 model sports a fantastic equipment at a very reasonable price and is very easy to install. One of its most convincing aspects is not only its small footprint but also the 1,3 megapixel image sensor that delivers crystal clear images. And the 2-way audio transmission provides an additional surveillance and communications tool from and to the camera. Finally, its powerful H.264 compression capabilities, WiFi and Ethernet connection, 3GPP Streaming and many more allow for an outstanding communication performance in every network.

HARDWARE

CPU	ARM 9, 32 bit RISC
RAM	64MB
Flash	8MB
Image sensor	1/4" (6,4mm) CMOS
Sensitivity	1.5 lux @F2.0
Supports DC Iris	-
I/O	-
Lens	4.0 mm, F2.0
Microphone	integrated
LED	-
IR distance	-
RS-485	-
Audio In	-
Audio Out	1 (3.5 mm Phone Jack)
Power over ethernet	-
Power consumption	DC 12V 200mA WIFI: DC 12 250mA
Operating temperature	0°C ~ 60°C
Dimensions	140mm(Ø) x 130mm (H)
Weight	180g

NETWORK

Network protocols	HTTP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP
Ethernet	10/ 100 Base-T
Wireless	802.11b/g
Security	WEP, WPA-PSK, WPA2-PSK

SYSTEM

Video resolution	1280x1024, 640x480, 320x240, 160x120
Video adjustment	Brightness, contrast, sharpness, BLC, night mode
Dual Streaming	Yes
Screenshots	Yes
Fullscreen	Yes
Compression format	H.264/ MJPEG / MPEG4 (3GPP only)
Video Bitrates adjustment	CBR, VBR
Movement recognition	Yes 3 areas
Actionable items	Mail, FTP
Pre/ Post alarm	Yes, adjustable
Security	Password protected
Firmware Upgrade	HTTP Modus, upgradable via remote control
Multiuser access	Yes, up to ten parallel user
Audio	Yes 2-way
SD card recording	Movement detection, check IP, network down (Ethernet only), schedule, relay out
SD-Video Format	AVI, JPEG
Playback	Yes
Wipe data	Yes

SYSTEM REQUIREMENTS

Operating System	Windows 2000, XP, 2003, Microsoft IE 6.0 or higher
Hardware recommended	Intel Dual Core 1.66G, RAM: 1024MB, graphics card: 128MB
Hardware minimum	Intel-C 2,8G, RAM:512MB, graphics card: 64MB

SCOPE OF DELIVERY

LupusnetHD Network Camera Model	LE950
Mount	Included
Power adapter	12V 1A
Software	LupusnetHD Lite
User manual	Quick User Manual for camera, User manual for Software and camera on CD

Your LUPUS Certified Partner:

